



## Especificaciones

Model		SH116-CH16
Sistema Operativo		Embedded LINUX
Video	Compresion	H.264
	Entradas	16ch BNC (1.0 Vp-p,75Ω)
	Salidas	1 BNC, 1 VGA
	Dual Stream	Si
Audio	Compresion	G.711A
	Entradas	2ch BNC
	Salidas	1ch BNC
	Bidirectional Talk	1ch in / 1 ch out (3.5mm MIC interface)
Alarma	Entradas	4
	Salidas	1
Preview	Resolucion	BNC : D1, 704x576(PAL)/704x480(NTSC)    VGA:1280X1024
	Display	1ch/ 4ch / 9 ch / 16ch
	Sequencer	Si
	Privacy Masking	4 zones Maximum, On DVR
Recording	Resolucion	16CIF
	Modo Grabacion	Manual, Schedule, Motion, Alarm
	Calidad Grabacion	CBR, VBR
	Intervalos de Grabacion	Pre-record: 5~30 sec., Post-record: 0~180sec.
Playback	Canales	1ch/16c
	Modo Busqueda	Time, Date, Record Mode, Smart search
	Privacy Masking	4 zones Maximum, On DVR and PC
Red	Operación Remota	WEB( IE, Google, Firefox)
Email		Test and send
Mobile		Soporta (IPhone, Android, Ipad/ Windows Mobile, Symbian, BlackBerry)
Backup		USB & Network
HDD		1HDD(Max 2TB)
Interface Externa	Ethernet	RJ45 10M/100M Ethernet Interface
	USB	2 ports( Mouse & Backup)
	Serie	N/A
General	Alimentacion	220±30% V,50±3% Hz / 110±20% V,60±3% Hz
	Consumo(sin HDD)	10W
	Temp Trabajo	-10℃-45℃
	Dimensiones	324mm×245mm×47mm(W×D×H)
	Peso	4KG(sin HDD)